

## Island Ventilation Hood

DA 5106 D



# Island Ventilation Hood DA 5106 D



## FEATURES

- NEW: LED ClearView lighting
- NEW: Con@ctivity — communication between hood and cooktop
- NEW: Telescopic chimney
- NEW: Recirculating as option
- Four fan speeds (incl. intensive)
- Delayed shutdown for 5 or 15 minutes
- Programmable filter saturation timers
- Stainless steel finish
- Polished steel logo
- Automatic shutdown of intensive level, programmable for 10 minutes

## SPECIFICATIONS

**DA 5106 D — Item 28510655USA**

Vented or Recirculating	625 CFM setting
Canopy Dimensions	39 <sup>3</sup> / <sub>8</sub> " (1000 mm) W x 4 <sup>1</sup> / <sub>2</sub> " (115 mm) H x 27 <sup>9</sup> / <sub>16</sub> " (700 mm) D
Dimensions (Standard Height) - Vented	29 <sup>1</sup> / <sub>8</sub> " — 40 <sup>3</sup> / <sub>16</sub> " (740—1020mm) H
Dimensions (Standard Height) - Recirculating	31 <sup>1</sup> / <sub>2</sub> " — 43 <sup>3</sup> / <sub>4</sub> " (800—1110mm) H
Chimney Dimensions	12" (305mm) W x 11 <sup>5</sup> / <sub>8</sub> " (295mm) D
Minimum distance above cooktop	Please refer to page 26 of the installation manual
Color	Available in brushed stainless steel or RAL colors
<b>Electrical</b>	
Electrical Requirements	120 V, 60 Hz, 15 Amps
Electrical Rating	362 W (Blower: 350 W; Lighting: 4x3 W)
<b>Optional Accessories</b>	
Recirculating Kit	DUI 32 Recirculating Kit
OdorFree Charcoal Filter	DKF 12-1 OdorFree Charcoal Filter
Reducing Collar (air flow max. 400 CFM)	
<b>Shipping</b>	
Shipping Weight	90 lbs (41kg)
<b>Support</b>	
Call	800.843.7231
20/20	©2020technologies.com

