

## G 7366 SCVi SF

## 24" Fully Integrated Dishwasher

## Features:

- AutoDos an integrated automatic detergent dispensing system
- DirectSensor Controls intuitive touch controls
- QuickIntenseWash a full wash and dry cycle in 58 minutes
- 42 dB (40 dBa when using ExtraQuiet)
- 3D MultiFlex Cutlery Tray
- CleanTouch Steel easy to clean, fingerprint resistant stainless steel with ContourLine handle
- WifiConn@ct
- · Water Softener
- EnergyStar
- NEW ContourLine GEN 7000 handle



SPECIFICATIONS	
Overall Unit Dimensions	$23^{9}/_{16}$ " (598 mm) W x $33^{11}/_{16}$ " - $36^{1}/_{4}$ " (855 -920 mm) H x $22^{7}/_{16}$ " (570 mm) D [Depth does not include door panel]
Niche	
Minimum Cabinet Niche Opening	23 <sup>5</sup> / <sub>8</sub> " (600 mm) W x 33 <sup>3</sup> / <sub>4</sub> " (857 mm) H x 22 <sup>7</sup> / <sub>16</sub> " (570 mm) D
Plumbing	
Water Supply Requirements	<ul> <li>Cold or Hot (max 150°F/65°C)         water connection</li> <li>Male 3/8" compression fitting</li> <li>Water pressure range 7.25 psi (0.5 bar) and 145 psi (10 bar)</li> </ul>
Water Connection Line (Supplied)	Length: 5 ft (1.5 m) Female 3/8" compression.
Drain Hose (Supplied)	Length: 5 ft (1.5 m) 7/8" (22 mm) internal diameter
Electrical	
Electrical Requirements	110V / 120V, 60Hz, 15 Amps
Power Cord (Convertible to hardwire)	NEMA 5-15 plug, 5 ft (1.52 m)
Shipping	
Shipping Weight	121 lbs (55 kg)
Shipping Dimensions	27¹/₅" W x 38¹/₅" H x 26³/₅" D



## PRODUCT AND CUTOUT DIMENSIONS

