

ESW 7670 - Obsidian Black

30" Handless Warming Drawer - VitroLine


Features:

- Keep food or plates and cups warm
- Fits 12 place settings
- Non-Slip Liner
- Control Panel with sensor controls




| MATERIAL # | UMRP | RETAIL |
|------------|---------|--------|
| 11794840 | \$2,499 | tbd. |

| SPECIFICATIONS | |
|--|---|
| Overall Unit Dimensions | 29 ¹³ / ₁₆ " (757 mm) W x 9 ³ / ₄ " (248 mm) H x 21 ³ / ₄ " (542 mm) D |
| Niche | |
| Cabinet Niche Opening with Combination Appliance | 21 ¹ / ₂ " (724 mm) W x Combination Appliance Opening Height + 9 ³ / ₄ " (248 mm) H x 24" (610 mm) D |
| Electrical | |
| Electrical Requirements | 120V, 60Hz, 15 Amps |
| Power Cord | NEMA 5-15 plug, 5 ft (1.52 m) |
| Shipping | |
| Shipping Weight | 70.5 lbs (32 kg) |
| Shipping Dimensions | 28 ³ / ₈ " (745 mm) W x 14 ⁹ / ₁₆ " (370 mm) H x 33 ⁵ / ₁₆ " (845 mm) D |






E = Electrical connection

Front View



Side View




①- Electrical and water supplies are recommended to be placed in adjacent cabinetry.




 mieleusa.com

PROUD CUTOUT DIMENSIONS

Front View



Side View



A - Cut-out (4" x 28" [100 mm x 720 mm]) in the bottom of the cabinet for the power cord and Ventilation

ⓘ - Electrical and water supplies are recommended to be placed in adjacent cabinetry.

Additional cabinet depth is required when placing the electrical and water supplies behind the appliance.