

ESW 7580

30" Handless Warming Drawer - ContourLine

Features:

- Keep food or plates and cups warm
- Fits 12 place settings
- Non-Slip Liner
- Control Panel with sensor controls





MATERIAL

11794800


| SPECIFICATIONS | |
|-------------------------------|---|
| Overall Unit Dimensions | 29 ¹³ / ₁₆ " (757 mm) W x 10 ¹³ / ₁₆ " (275 mm) H x 23 ⁷ / ₈ " (608 mm) D |
| Niche | |
| Minimum Cabinet Niche Opening | 28 ⁵ / ₈ " (724 mm) W x 10 ⁵ / ₈ " (270 mm) H x 24" (610 mm) D |
| Electrical | |
| Electrical Requirements | 120V, 60Hz, 15 Amps |
| Power Cord | NEMA 5-15 plug, 5 ft (1.52 m) |
| Shipping | |
| Shipping Weight | 74.3 lbs (33.7 kg) |
| Shipping Dimensions | 33 ⁵ / ₁₆ " (845 mm) W x 14 ⁹ / ₁₆ " (370 mm) H x 29 ³ / ₈ " (745 mm) D |

PRODUCT DIMENSIONS





FLUSH CUTOUT DIMENSIONS

Front View




Side View





- A - Cut-out (4" x 28" [100 mm x 720 mm]) in the bottom of the cabinet for the power cord and Ventilation
- ⚠ - Electrical and water supplies are recommended to be placed in adjacent cabinetry.
Additional cabinet depth is required when placing the electrical and water supplies behind the appliance.

PROUD CUTOUT DIMENSIONS

Front View



Side View



A - Cut-out (4" x 28" [100 mm x 720 mm]) in the bottom of the cabinet for the power cord and Ventilation

⚠ - Electrical and water supplies are recommended to be placed in adjacent cabinetry.

Additional cabinet depth is required when placing the electrical and water supplies behind the appliance.