

## ESW 7680

### 30" Handless Warming Drawer - PureLine

#### Features:

- Keep food or plates and cups warm
- Fits 12 place settings
- Non-Slip Liner
- Control Panel with sensor controls





#### MATERIAL #

11794860


SPECIFICATIONS	
Overall Unit Dimensions	29 <sup>13</sup> / <sub>16</sub> " (757 mm) W x 10 <sup>13</sup> / <sub>16</sub> " (275 mm) H x 23 <sup>7</sup> / <sub>8</sub> " (608 mm) D
Niche	
Minimum Cabinet Niche Opening	28 <sup>5</sup> / <sub>8</sub> " (724 mm) W x 10 <sup>5</sup> / <sub>8</sub> " (270 mm) H x 24" (610 mm) D
Electrical	
Electrical Requirements	120V, 60Hz, 15 Amps
Power Cord	NEMA 5-15 plug, 5 ft (1.52 m)
Shipping	
Shipping Weight	74.3 lbs (33.7 kg)
Shipping Dimensions	33 <sup>5</sup> / <sub>16</sub> " (845 mm) W x 14 <sup>9</sup> / <sub>16</sub> " (370 mm) H x 29 <sup>3</sup> / <sub>8</sub> " (745 mm) D

#### PRODUCT DIMENSIONS





## FLUSH CUTOUT DIMENSIONS

Front View




Side View





- A - Cut-out (4" x 28" [100 mm x 720 mm]) in the bottom of the cabinet for the power cord and Ventilation
- ⚠ - Electrical and water supplies are recommended to be placed in adjacent cabinetry.  
Additional cabinet depth is required when placing the electrical and water supplies behind the appliance.

## PROUD CUTOUT DIMENSIONS

Front View



Side View



A - Cut-out (4" x 28" [100 mm x 720 mm]) in the bottom of the cabinet for the power cord and Ventilation

ⓘ - Electrical and water supplies are recommended to be placed in adjacent cabinetry.

Additional cabinet depth is required when placing the electrical and water supplies behind the appliance.