

ESW 6380

30" Handless Warming Drawer - Fully Integrated

Features:

- Keep food or plates and cups warm
- Fits 12 place settings
- Non-Slip Liner
- Control Panel with sensor controls





MATERIAL

9685060


SPECIFICATIONS	
Overall Unit Dimensions	29 ¹³ / ₁₆ " (757 mm) W x 10 ¹³ / ₁₆ " (275 mm) H x 24 ³ / ₄ " (629 mm) D
Niche	
Minimum Cabinet Niche Opening	28 ⁵ / ₈ " (724 mm) W x 10 ⁵ / ₈ " (270 mm) H x 24" (610 mm) D
Electrical	
Electrical Requirements	120V, 60Hz, 15 Amps
Power Cord	NEMA 5-15 plug, 5 ft (1.52 m)
Shipping	
Shipping Weight	70 lbs (31.7 kg)
Shipping Dimensions	33 ⁵ / ₁₆ " (845 mm) W x 14 ⁹ / ₁₆ " (370 mm) H x 29 ³ / ₈ " (745 mm) D

PRODUCT DIMENSIONS





FLUSH CUTOUT DIMENSIONS

Front View




Side View





- A - Cut-out (4" x 28" [100 mm x 720 mm]) in the bottom of the cabinet for the power cord and Ventilation
- ⚠ - Electrical and water supplies are recommended to be placed in adjacent cabinetry.
Additional cabinet depth is required when placing the electrical and water supplies behind the appliance.

PROUD CUTOUT DIMENSIONS

Front View



Side View




A - Cut-out (4" x 28" [100 mm x 720 mm]) in the bottom of the cabinet for the power cord and Ventilation

⚠ - Electrical and water supplies are recommended to be placed in adjacent cabinetry.

Additional cabinet depth is required when placing the electrical and water supplies behind the appliance.

CUSTOM PANEL DETAILS

The front panel must be at least 3/4" (19 mm) thick and made of heat resistant material 140° F (60° C). The front panel, including handle, must not exceed 11 lb (5 kg) in weight.



- Mounting hole diameter: 3/8"
- Minimum custom front panel width: 29 13/16"